



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04M 3/00, 5/00, 7/00	A1	(11) International Publication Number: WO 98/37687 (43) International Publication Date: 27 August 1998 (27.08.98)
(21) International Application Number: PCT/US98/02847 (22) International Filing Date: 17 February 1998 (17.02.98) (30) Priority Data: 08/802,660 19 February 1997 (19.02.97) US (71) Applicant: GENESYS TELECOMMUNICATIONS LABORATORIES, INC. [US/US]; 11th floor, 1155 Market Street, San Francisco, CA 94103 (US). (72) Inventor: MILOSLAVSKY, Alec; 10 Whitman Court, San Carlos, CA 94070 (US). (74) Agent: BOYS, Donald, R.; P.O. Box 187, Aromas, CA 95004 (US).		(81) Designated States: AU, CA, CN, JP, KR, RU, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: APPARATUS AND METHODS ENHANCING CALL ROUTING TO AND WITHIN CALL-CENTERS

(57) Abstract

A computerized telephony call center for serving a customer base has a central switch connected to a plurality of telephones (136, 138, 140, 142) at operator workstations (331, 332) and adapted to route calls to individual ones of the telephones, and also connected to a public switched telephone network (100), and a first processor (223) connected to the central switch (123, 124) by a high-speed data link (212, 213) and to the telephone network by a digital network connection. The first processor is adapted to monitor transactional activity of the central switch, to process the activity information according to selected routines in the processor, and to communicate processed information to a second processor (224) over the digital network connection. The first processor is connected by a LAN (301) to network interfaces including a video display unit and input apparatus proximate individual ones of the plurality of telephones connected to the central switch. The LAN is also connected to a data server (303) running an instance of a database. The call centers are all part of a call routing system wherein calls are routed from Service Control Points (101) to call centers over telephone lines, and data is routed to the call centers over a separate digital network connection between processors coupled to the SCPs and to the call center central switches.

